



STERIPLUS™ 80

**INTEGRATED SYSTEM WITH
PRELIMINARY SHREDDING
AND STEAM STERILIZATION
OF YOUR BIOHAZARDOUS
WASTE**

The **STERIPLUS™** systems from **Tesalys** are the ideal solution to inactivate your biohazardous waste safely on-site. Its integrated shredding system **TESASHRED™** not only reduces the volume and mass of waste, but also ensures waste is fully processed.

TESALYS

Main address
7, rue du Cassé
31240 Saint-Jean (Toulouse)
France

Tel. +33 5 62 10 18 91
info@tesalys.fr

www.tesalys.fr



STERIPLUS™ 80

integrated system with preliminary shredding and steam sterilization of your biohazardous waste



UTILITIES

WATER

REQUIREMENTS	Softened water 4-8° TH
CONSUMPTION	15 liters / cycle

ELECTRICITY

REQUIREMENTS	380-400 V III N, 50Hz/60Hz, 20 kW
CONSUMPTION	3.5 kW/h / cycle

DRAIN	32 mm Ø internal (heat-resistant)
-------	-----------------------------------

STEAM/COMPRESSED AIR

Produced by the integrated steam generator and air compressor; no external connection required.

(1) 30-35min for test loads as per NF X30-503-1 standard.

(2) Cycle times may vary based on the type of materials, waste density, humidity, quantity of liquids, etc. For loads with high liquid content, cycle time can be longer. Up to 50min depending on the waste density.

(3) Based on an average cycle time of 45min. (40 min. of cycle + 5 min. unloading/loading time).

(4) Quantity of liquids allowed might vary depending on application (urine bags, blood bags, food testing bags, ...). All the data given in this catalogue are non-binding and given as a guide only. Treatment capacities, cycle times and consumptions are given as mere examples and may vary depending on the type of waste, installation conditions, operator's availability and skills.

Consumption is calculated on the basis of a standard cycle of the machine.

For consumption with cooling of the drain and / or the Virus + kit, please consult us.

LOADING CHAMBER CAPACITY

80 L

LOADING CHAMBER USEFUL DIMENSIONS (W x D x H)

370 x 360 x 628 mm

LOADING CAPACITY (CONTAINERS)

1 X TESABOX 80
or 2 X TESABOX 40
or 4 X TESABOX 20

TOTAL CYCLE TIME (NF X30-503-1 STANDARD) (1)

30 to 35 min

TOTAL CYCLE TIME IN WORKING CONDITIONS (2)

30 to 50 min

LOADING CAPACITY (KG/CYCLE)

Based on an average waste density of 0,08 to 0,12kg/L for Healthcare Waste

6,4 to 9,6 kg/cycle

Based on an average waste density of 0,12 to 0,2kg/L for Lab/Humid/Liquid Waste

9,6 to 16 kg/cycle

TREATMENT CAPACITY (KG / H) (3)

Based on an average waste density of 0,08 to 0,12kg/L for Healthcare Waste

8 to 12 kg/h

Based on an average waste density of 0,12 to 0,2kg/L for Lab/Humid/Liquid Waste

12 to 20 kg/h

MAX QUANTITY OF LIQUID RECOMMENDED PER CYCLE (4)

24 L

EXTERNAL DIMENSIONS (W x D x H)

1550 x 1200 x 1800 mm

NET WEIGHT

1300 kg

LOADING CHAMBER

Stainless steel with PTFE coating

TREATMENT CHAMBER

AISI 304L stainless steel

STEAM GENERATOR

AISI 304L stainless steel (chamber) & Highly corrosion-resistant Hastelloy®

WATER SOFTENER

Built-in

WATER BOOSTER PUMP AND AIR COMPRESSOR

Built-in

WASTE SHREDDER

Structure: AISI 304L stainless steel & Blades: High-strength steel

PIPING

Stainless steel/PTFE flexible hosing

CHASSIS

Painted steel

BODYWORK

Composite material/Painted steel

CYCLE TRACEABILITY Through printout

Built-in

USB PORT

Built-in

STERIPLUS™ A COMPLETE RANGE



STERIPLUS™ 20
2/5 kg/h



STERIPLUS™ 40
4/10 kg/h



STERIPLUS™ 80
8/20 kg/h



TESABAG
Autoclavable
biohazardous waste bags



TESABOX
Cardboard containers
for biohazardous waste